



Nitrile

Durable protection in a comfortable, versatile glove

- Versatile disposable glove ideal for a wide variety of industrial applications
- Textured throughout the palm to ensure good grip in wet, dry and oily environment
- Silicone-free for better product protection
- Tested for use with chemotherapy drugs



Industries

- Automotive
- Chemical
- Machinery and Equipment
- Life Sciences
- Food Processing

Recommended For

- Assembly and inspection of components
- Light assembly tasks
- Handling of paint/glue guns and sprayers
- Chemical Handling
- Cleaning of plant and machines
- Blending, compounding materials
- Equipment repair and maintenance
- Handling of tools
- Maintenance
- Laboratory analysis
- Transferring liquids and solids
- Sample taking and processing
- Food processing and handling



TECHNICAL DATA SHEET

PRODUCT INFORMATION

	93-143
Material	Nitrile
Color	Blue
Glove Design	Chlorinated, Powder-Free, Fully Textured
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 9001:2008
Regulatory/Standards Compliance	ASTM D6319, Category III, EAC TP TC 019:2011, EC 1935/2004, EC 2002/72, EC 2023/2006, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN 420:2003 + A1:2009, EN ISO 374-5:2016, FDA21 CFR 177-2600, ISO 13485
Packaging	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
User Needs Segment	Multi-Purpose
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Sensitisers	<ul style="list-style-type: none"> Zinc Dibutyldithiocarbamate (ZDBC) Zinc Diethyldithiocarbamate (ZDEC) <p><i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i></p>

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767, EN420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151, EN 374-2
Palm Thickness (mm/mils)	0.11 / 4.3		ASTM D3767, EN420
Finger Thickness (mm/mils)	0.12 / 4.7		ASTM D3767, EN420
	BEFORE AGING		AFTER AGING
Ultimate Tensile Strength (MPa)	22	14	ASTM D412 & D573
Elongation at Break (%)	500	400	ASTM D412
Force at break (N)	6	6	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Ansell Product Code	93143060	93143070	93143080	93143090	931430100

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
(Malaysia) Sdn Bhd
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

