

Versatile chemical protection that performs across a diverse range of applications

- High performance nitrile compound provides an outstanding combination of chemical resistance and strength.
- The glove offers a far superior snag, puncture and abrasion protection compared with rubber or neoprene gloves
- Will not swell, weaken or degrade, and does not promote contact dermatitis
- High levels of flexibility, comfort and dexterity.
- Suitable for heavy-duty cleaning applications

Industries

- Automotive
- Machinery and Equipment
- Chemical

Applications

- Handling rough machined metal parts
- Equipment repair & maintenance
- Painting or cleaning tools or robots
- Changing tools and dies
- Handling incoming goods
- Filling, blending and charging of raw materials
- Opening and draining pumps valves or lines
- Loading and unloading of process equipment
- Transferring liquids and solids between vessels and tanks and process equipment
- Supervision of running operation
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Testing
- Opening furnaces draining pumps valves or lines and crackers BTX process



AlphaTec® Solvex®

37-165

Excellent chemical protection with a good level of grip, fit and comfort

Key Features

- No inner cotton flocking ,reducing risk of lint contamination and making it ideal for production areas sensitive to the introduction of external impurities.
- Sandpatch finish giving the glove a smooth surface that decreases indirect costs ,thanks to fewer rejects of fragile parts
- Fully reusable, with an unequaled abrasion resistance
- Provides superb comfort for the wearer
- Complies with FDA food handling requirements (21 CFR 177.2600).
- Combining superb value and quality.

Performance Standards



ABR



0086



AGJKLPT



A K L



4102X

EN 388:2003



4102



CHEMICAL AGENT	BREAKTHROUGH TIME
Methanol (A)	134 (palm)
Diethylamine (G)	55 (palm)
n-Heptane (J)	>480 (palm)
Sodium hydroxide, 40% (K)	>480 (palm)
Sulphuric acid, 96% (L)	165 (palm)
Hydrogene peroxide, 30% (P)	>368 (palm)
Formaldehyde, 37% (T)	>480 (palm)

PERMEATION BREAKTHROUGH TIMES ACCORDING TO EN 16523-1 : 2015 (MINUTES)						
0	1	2	3	4	5	6
< 10	10-30	30-60	60-120	120-240	240-480	> 480
Not recommended	Splash protection		Medium protection		High protection	

Data given in the table above are based on results of laboratory tests performed on the palm area of the glove. These tests were run using standard test methods that may not adequately replicate any specific conditions of end use. Because Ansell has no detailed knowledge or control over the conditions of end use, any of these data must be advisory only, and Ansell must decline any liability.

Specifications

BRAND STYLE	DESCRIPTION	SIZE	LENGTH	COLOR	PACKAGE
AlphaTec® Solvex® 37-165	N/A, Nitrile,	7, 8, 9, 10, 11	380 mm/ 15 inches	Green	• 12 pairs per inner bag, 6 inner bags per case (72 Pairs)

North America Region
Ansell Healthcare Products LLC
111 Wood Avenue South,
Suite 210
Iselin, NJ 08830, USA
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
Ansell Commercial Mexico S.A. de C.V.
Blvd. Bernardo Quintana No. 7001-C,
Q7001 Torre II.
Suites 1304, 1305 y 1306.
Col. Centro Sur, c.p. 76079
Queretaro, Qro. Mexico
T: +52 442 248 1544 / 248 3133

Canada
Ansell Canada Inc.
105, rue Lauder
Cowansville (Québec)
Q7001 Torre II.
J2K 2K8, Canada
T: 1 800 363-8340
F: 1 888 267-3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending:
www.ansell.com/patentmarking © 2018 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

Ansell