RUSH+ SMALL SEAL

RUSH+ Small Seal adopts all the features of RUSH+ Seal just in a smaller fit & with maximum protection.





1672301FB • Clear Lens





1672302FB • Smoke Lens



- **+** ♦ PLATINUM® COATING (+ P)
- + ADJUSTABLE PVC NOSE BRIDGE PLUS
 CO-MOULDED TEMPLE ARMS FOR SUPERIOR
 COMFORT AND GRIP
- + 'POSITIVE SEAL' GASKET AND STRAP KIT TO

 MAXIMISE PROTECTION IN DUSTY ENVIRONMENTS

- **+** ULTRA LIGHTWEIGHT
- **+** BUILT IN BROW PROTECTION
- + SMALL FIT



RUSH+ SMALL SEAL

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH+ SMALL	Clear	1672301FB	Ю	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum ⁺₽
SEAL	Smoke	1672302FB	13	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum +

LENS MARKING

- **7.** Platinum is permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear)
- 3. Range of luminous transmittance 8 -18% (smoke).

LENSES

- 2mm polycarbonate
- 9 base curve
- Platinum coating on both sides of Clear and Smoke
- 100% UV 385 Clear
- 100% UV 400 Smoke

FRAME MARKING

AS/NZS 1337.1.2010: Tested and approved to. AS/NZS 1337.1.2010 - Medium Impact & chemical splash protection

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS			
LENSES	PC - 2,2 mm - Curve 9		
FRAME	PC		
TEMPLES	PC + TPR		
STRAP	Nylon		
FOAM	Yes		
SPARE LENSES	No		

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd 32-40 Fairchild Street Heatherton VIC 3202 T: 1300 138 098 E: safety@bolle.com.au NEW ZEALAND:

T.: 0800 2655 369 E: bolle@bolle.co.nz

