

Product Family

Honeywell Howard Leight™ X-TREME™ Disposable Earplug

The Honeywell Howard Leight X-TREME earplug is a low cost, reliable alternative to your current foam earplugs. The signature bright orange tapered shape design is available in both corded and uncorded versions. The X-TREME has a higher attenuation, at 32 dB, than most disposable foam earplugs on the market.

Learn more about our products at howardleight.com



Product Numbers & Ordering Information Product Numbers Details XTR-1 Honeywell Howard Leight™ X-TREME™ Disposable Earplug Uncorded XTR-30 Honeywell Howard Leight™ X-TREME™ Disposable Earplug Corded HL400-XTR-INTRO Honeywell Howard Leight™ X-TREME™ Disposable Earplug HL400 Intro Kit HL400-XTR-REFILL Honeywell Howard Leight™ X-TREME™ Disposable Earplug HL400 Prefilled Canisters (2 per case) XTR-LS4-REFILL Honeywell Howard Leight™ X-TREME™ Disposable Earplug HL400 & LS400 Refill Zip Top Bag

Overview

Key Features

• Comfortable earplug with high attenuation

Honeywell Howard Leight X-Treme Earplug

- Easy insertion and removal with smooth tapered shape design
- Bright color offering high visibility and worker compliance
- Corded version helps to guard against the earplugs falling onto the floor
- Bulk refill options for dispensers available

Recommended Industries/Use

- Other Agriculture Construction Forestry Government Law Enforcement
 Manufacturing Medical Military Mining Municipal Services Oil and Gas
- Pharmaceutical
 Steel and Metals
 Transportation
 Utilities
 Welding
 Wind Energy

Hazards

Noise

Regulations

• USA - EPA Certified

Specifications

Box

• 200 pairs (XTR-1), 100 pairs (XTR-30)

Case

• 10 boxes

Pallet

• 45 cases

Box Dimensions

• L-8" H-7.75" D-5.1"

Case Dimensions

• L- 25.6" H-8.1" D-16.8"

Box Material

Cardboard

Case Material

• Corrugated Cardboard

NRR

• 32 dB

Material

• Polyurethane Foam

Literature & Documents

Hearing_HowardLeight_XTREME_Flyer http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection /4294999317/1033.aspx

Training & Proper Use

Refer to User Instructions for use.

Technical Support

800-873-5242