MUTEX LIGHT+ PROTECTIVE COVERALLS

Honeywell Mutex® Light+ single-use protective coveralls are designed to protect against solid particles and small splashes, including biological/infective agents.



Elasticated wrists and ankles



3-piece elasticated hood



seams



Anti-static, silicon and latex free



Dual slider zippers



Tear resistant

ENHANCED PROTECTION AND ERGONOMICS

- Chemical protection Type 5 and 6, Category III
- · Certified against biological agents
- Good resistance to tearing and liquid penetration
- Polypropylene laminated with a micro-porous film. Weight: 65g/m³

ERGONOMICS OF HONEYWELL COVERALLS

The Honeywell range of single-use protective coveralls include Mutex* E-light, Mutex* Light+, Spacel* C4 and Spacel* C Medium. While each product provides different levels of protection, they share the following features.

- Lightweight and comfortable
- Tear resistant crotch design
- 3-piece elasticated hood
- Silicone and latex free
- Dual slider zip
- · Elasticated wrists and ankles



APPLICATIONS

- Disease protection
- Asbestos inspection
- Chemical/Petrochemical industry
- Construction/Building and public works
- Landscaping/Painting/DIY
- Light industrial cleaning and maintenance
- Pharmaceutical industry
- Waste disposal



MUTEX® LIGHT+ PROTECTIVE COVERALLS

Mutex* Light+ single-use protective coveralls are designed to protect against solid particles and small splashes, including biological/infective agents. Featuring Type 5 and 6, Category III certification, so you can be assured of the best protection.

STANDARDS AND COMPLIANCE













PARTICLES
DOES NOT
PROTECT AGAINS
RADIATION

E CATEGORY III PPE COMPLIANCE WITH REGULATION IST (EU) 2016/425

PERFORMANCES		NORMS	CLASS
TYPE 5	LIMITED LIFE, FULL BODY CHEMICAL PROTECTIVE CLOTHING AGAINST SOLID PARTICLES	EN ISO 13982- 1+A1:2010	PASS Ljmn, 82/90 ≤ 30% Ls, 8/10 ≤ 15%
TYPE 6	LIMITED LIFE FULL BODY CHEMICAL PROTECTIVE CLOTHING AGAINST LIQUIDS	EN 13034+ A1:2009	PASS
INWARD LEAKAGE	NON VENTILATED PROTECTIVE CLOTHING AGAINST PARTICULATE RADIOACTIVE CONTAMINATION	EN 1073-2:2002	CLASS 2

ORDERING INFORMATION

PART NO.	DESCRIPTION	COLOUR	SIZE	HEIGHT (CM) A	CHEST (CM) B	PACKAGING	CARTON DIMENSIONS
4500501-S	MUTEX® LIGHT+	WHITE	S	164-170	84-92	25 EACH PER CARTON - INDIVIDUALLY PACKED	48 x 33 x 30cm
4500501-M	MUTEX® LIGHT+	WHITE	М	170-176	92-100	25 EACH PER CARTON - INDIVIDUALLY PACKED	48 x 33 x 30cm
4500501-L	MUTEX® LIGHT+	WHITE	L	176-182	100-108	25 EACH PER CARTON - INDIVIDUALLY PACKED	48 x 33 x 30cm
4500501-XL	MUTEX® LIGHT+	WHITE	XL	182-188	108-116	25 EACH PER CARTON - INDIVIDUALLY PACKED	48 x 33 x 30cm
4500501-XXL	MUTEX® LIGHT+	WHITE	XXL	188-194	116-124	25 EACH PER CARTON - INDIVIDUALLY PACKED	48 x 33 x 32cm
4500501-XXXL	MUTEX* LIGHT+	WHITE	XXXL	194-200	124-132	25 EACH PER CARTON - INDIVIDUALLY PACKED	48 x 33 x 36cm

CARE INSTRUCTIONS

Discard after use. Maximum recommended period of use - not more than a continuous period of one working day.

LIMITATION OF USE

Do not use the coveralls if it is defective i.e. defective closing system, open seams, scratches, tears or holes.

STORAGE AND SHELF LIFE

Store between -10°C to +40°C in its original packaging and carton. Optimal product use is ensured three years from date of manufacture.

For More Information

www.honeywellsafety.com

Honeywell Safety Products Australia Pty Ltd

45 Grosvenor Street,
Abbotsford, Victoria 3067
Australia Tel: 1300 139 166
New Zealand Tel: 0800 322 200
Email: hspspacific@honeywell.com

THE FUTURE IS WHAT WE MAKE IT

